



Claims Listing

1. (Amended). An improved telescoping stun gun comprising:

- a. a handle comprising a power source electrically connected to a voltage step-up circuit having an output of stepped-up voltage relative to the power source;
- b. a first tube section having a base section and a distal end, said base section being connected to the handle;
- c. at least one additional tube section having a proximal end and a distal end and being disposed within the first tube section, said distal end comprising a conductive probe electrically connected to the output of the step-up circuit, said probe for delivering a high-voltage shock, said proximal end of said at least one additional tube section having a diameter that is larger than the diameter of the distal end of the first tube section;
- d. deployment means to extend said at least one additional tube section from its position as being disposed within the first tube section to an extended position whereby when in its extended position, the proximal end of the at least one additional tube section frictionally connects to the distal end of the first tube section; and
- e. a first conductive lead electrically connected to the conductive probe, said first conductive lead being attached to the outside of the at least one additional tube section.

Claim 2 is canceled.

3. (Original). The improved telescoping stun gun of claim 1 wherein the first tube section is tapered along its entire length, the large end of the taper being at the base of the first tube section.

4. (Original). The improved telescoping stun gun of claim 1 wherein both the first tube section and the at least one additional tube section are tapered whereby the outer diameter of the proximal end of the at least one additional tube section is slightly larger in diameter than the inner diameter of the distal end of the first tube section.

Claim 5 has been canceled.

6. (Amended). The improved telescoping stun gun of claim 1 further comprising a second conductive lead electrically connected to the conductive probe, said second conductive lead being placed along the exterior of the first tube section.

7. (Amended). The improved telescoping stun gun of claim 1 wherein the conductive probe is electrically connected to the output of the step-up circuit through the first conductive lead.

8. (Original). The improved telescoping stun gun of claim 1 wherein the conductive probe is electrically connected to the output of the step-up circuit through one or more wires contained internally within the first tube section and the at least one additional tube section.

9. (Original). The improved telescoping stun gun of claim 1 wherein the conductive probe extends from the distal end of the at least one additional tube section.

10. (Amended). An improved telescoping stun gun comprising:

- a. a first tube section having a base section and a distal end, said first tube section comprising a power source electrically connected to a voltage step-up circuit having an output of stepped-up voltage relative to the power source;
- b. at least one additional tube section having a proximal end and a distal end and being disposed within the first tube section said distal end comprising a conductive

probe electrically connected to the output of the step-up circuit, said probe for delivering a high-voltage shock, said proximal end of said at least one additional tube section having a diameter that is larger than the diameter of the distal end of the first tube section;

c. deployment means to extend said at least one additional tube section from its position as being disposed within the first tube section to an extended position whereby, when in the extended position, the proximal end of the at least one additional tube section frictionally connects to the distal end of the first tube section;

d. a first conductive lead electrically connected to the output circuit and to the probe, said first conductive lead attached to the outside of the at least one additional tube section.

Claim 11 has been canceled.

12. (Amended). The improved telescoping stun gun of claim 10 further comprising a second conductive lead electrically connected to the conductive probe, said second conductive lead being placed along the exterior of the first tube section.

13.(Amended). The improved telescoping stun gun of claim 10 wherein the conductive probe is electrically connected to the output of the step-up circuit through the first conductive lead.

Claims 14-18 have been canceled.

19. (Amended). An improved telescoping stun gun comprising:

- a. a first tube section having a base section and a distal end;
- b. at least one additional tube section having a proximal end and a distal end and being disposed within the first tube section, said at least one additional tube section comprising a power source electrically connected to a voltage step-up circuit having an

output of stepped-up voltage relative to the power source, said distal end comprising a conductive probe electrically connected to the output of the step-up circuit, said probe for delivering a high-voltage shock;

c. said proximal end of said at least one additional tube section having a diameter that is larger than the diameter of the distal end of the first tube section;

d. deployment means to extend said at least one additional tube section from its position as being disposed within the first tube section to an extended position whereby, when in the extended position, the proximal end of the at least one additional tube section frictionally connects to the distal end of the first tube section; and

e. a first conductive lead electrically connected to the conductive probe, said first conductive lead attached to the outside of the at least one additional tube section.

20. (New). The improved telescoping stun gun of Claim 1 wherein the stun gun is connected to a riot shield.

21. (New). The improved telescoping stun gun of Claim 20 wherein the handle of the stun gun is rotatably mounted to the riot shield.